

Mody swimming pool cleaners

The MODY SUBMERSIBLE SWIMMING POOL CLEANER has revolutionized the way we can clean swimming pool today. The modern concept of using an electric submersible pump connected to a wide suction nozzle, fitted with a spring actuated nylon brush effectively removes muck accumulated on the floor and walls of a pool. Water is cleaned through a SS strainer to trap large solids like stones and then filtered though double fine mesh filter bags that collect even the smallest particles leaving the recirculated water sparkling clean operated by extension rods. This light weight cleaner is both versatile and economical.

Available in three models:

- 1.1KW / 1.5 HP unit is recommended for swimming pools at bungalows and resort. (Also available in Single Phase)
- 1.5 KW / 2HP for large size swimming pools of hotels and clubs.

TECHNICAL SPECIFICATIONS:

MODEL	B 100	B 100S	B 200		
KW RATINGS	1.1	1.1	1.5		
PHASE	THREE PHASE	SINGLE PHASE	THREE PHASE		
CAPACITY	400	400	600		
(LPM)					
SHUT OFF	12	12	12		
HEAD (M)					
MOTOR	2 POLE CONTINUOUS DUTY				
	INDUCTION MOT	INDUCTION MOTOR			
INSULATION	CLASS "F"	CLASS "F"	CLASS "F"		
SPEED (RPM)	2800	2800	2800		
FULL LOAD	2.2	9.5	3.4		
CURRENT					
(AMPS)					
POWER CABLE	4 X 1.5 SQ. MM,	4 X 1.5 SQ. MM,	4 X 1.5 SQ. MM,		
	30M	30M	40M		
SHAFT SEAL	SINGLE MECHANICAL SEAL TC /				
	TC WITH SECONDARY INNER LIP				
	SEAL IN OIL CHAMBER				
IMPELLER	SEMI OPEN	SEMI OPEN	SEMI OPEN		
TYPE					
HOUSE OUTLET	50	50	50/63.5		
(MM)					
NOZZLE	450	450	650		
WIDHT (MM)					
WEIGHT IN	21	25	25		
AIR (KG)					
WEIGHT IN	13	15	15		
WATER (KG)					

MATERIAL OF CONSTRUCTION

OUTER AND STATOR CASING : EXTRUDED ALUMINIUM POTOR SHAFT : \$\$.431

ROTOR SHAFT : SS 431
IMPELLER : BRONZE
PROTECTION BAG : NYLON
SLUDGE BAG : NYLON
EXTENTION ROD : ALUMINIUM
STRAINER : SS

ACCESSORIES

<u>ITCCESSOTTES</u>			
MODEL	B 100S	B100S	B200
Cable (Length in mtrs.)	30	30	30
Sludge Bag (nos.)	1	1	2
Protection Bag (nos.)	1	1	0
2.5 mtr. Extention Rods	2	2	3
Cable Float(nos.)	3	3	3
Control panel	Optional	incl.	Optional
Hose Outlet (mm)Optional	50	50	63.5

DESIGN ADVANTAGES

- Absolutely no waste of water
 - Frames are covered with PVC liners to avoid damage to the pool tiles.
 - Light weight, easily maneuverable on adjustable nylon wheels in and out of the water.
- Can be used as dewatering pump when required.
- An inbuilt wall cleaner attachment is provided.
- Rugged submersible motor with outer mechanical seal of TC / TC and secondary inner lip seal.

SERVICE & MAINTENANCE

The coarse strainer and filter bags need cleaning in fresh water after every use. Inspection once a year under normal operating condition

NOTE

- 1. The weight of unit is without cable and accessories.
- 2. The hose outlet is optional and available at extra cost
- 3. The control panel is essential with B100 S.
- 4. The unit is also available for any combination of voltage and frequency on special request.





mody industries (F.C.) pvt. ltd.

Regd. Office & Factory :

Plot No. C-41, Road, #34, Wagle Industrial Estate, Thane - 400 604. Tel.: (022) 2581 1644, (022) 2582 3850 Fax : (022) 2582 8217 Email : sales@modypumps.com

Branch Office :

203, Bakshi House, 40-41 Nehru Place, New Delhi 110 019. Tel.: (011) 2644 4668, 2622 9512 Fax: (011) 2646 4228

Website: www.modypumps.com